





ASSEMBLY INSTRUCTIONS

T140 / T220/ T300






! Roll up your sleeves and set up the Softub! Do not use a razor knife to open the box. Use the claw end of a hammer to tear the flaps open.

2




These are the items you received and will need. Please note that the filter is probably already installed in the tub. Please leave it installed on the wall of the tub.



3


! Place the straps for the cover on the ground in an "X" pattern. The back side of the buckle should be facing up so the buckle attaches properly on the lock. The plumbing connectors need to be between the straps.



4






Verify the placement of the straps under the tub. You can dry-fit the cover at this point in time to make sure the straps are installed correctly. Line up the connectors on the power unit with the connectors on the tub. The power unit is not to be plugged in yet!




5



Twist the connectors on a clock-wise fashion until the connectors are snug and no threads are showing. Connect the light connector.




6



2-3 min.




Run the hose for 2 to 3 minutes in the garden, yard or down a drain before beginning to fill the tub. This will help to clear out any algae or debris that is in the hose. When done, begin filling the tub.




7






After filling the tub with about 2 inches of water, smooth out any wrinkles on the bottom of the liner by moving the liner around with your hands and fingers. Tucking the liner in the bottom edges helps to alleviate the wrinkles.






2 In.






! Make sure the filter is installed if not installed already. Soak filter in warm water prior to installing to ease the installation. Fill tub to a level 2 inches above the highest jet.


DO NOT PLUG IN THE TUB YET!







! Check the tub connections for leaks. Simply tighten the connectors a little more if there is a leak. Plug the tub in now.



10



! Check for leaks while the tub is running. If there are leaks, tighten the connectors. Now install the foam and vinyl connector covers.



11

! With the tub running check the chemical levels and adjust them as necessary as advised in the Water Care Guide. Open the air control on the control panel by rotating counter-clockwise for 15 minutes after adding the chemicals. After 15 minutes, close the air control by rotating it counter-clockwise until it stops and put the lid on the tub.

